# LogisticRegression

Module name: LogisticRegression

**Description:** Logistic regression using clinical data and .cls file **Author:** Yujin Hoshida (Broad Institute) gp-help@broad.mit.edu

**Date:** 5/2/2006

Release: 1.0

**Summary:** Once a genomics marker or predictive model for clinical outcome is built, the next step is to test whether it really associates with outcome of new cohorts, or whether it has better predictive ability compared to already known clinical markers/predictive models. "Survival analysis" modules perform such analyses seamlessly after clustering/marker gene/prediction analyses.

Logistic regression is a commonly used to assess association of variable(s) of interest with binary clinical data (e.g., treatment response) [1-3]. For the LogisticRegression module, a .cls file identifies the phenotype label for each sample and a separate tab-delimited text file defines all other clinical variables. The module generates a result file similar to the one shown below. Interpreting the results requires basic knowledge of biostatistics and clinical data analysis.

(Dispersion parameter for binomial family taken to be 1)

Null deviance: 136.058 on 99 degrees of freedom Residual deviance: 89.814 on 98 degrees of freedom

AIC: 93.814

Number of Fisher Scoring iterations: 4

Deviance: 89.8139890522869

Estimate Std. Error Wald OR lower.95%.CI

(Intercept) 1.045969 0.3224127 3.244192 2.84615385

1.51291723

factor(cls)2 -3.243193 0.5710828 -5.679025 0.03903904

0.01274629

upper.95%.CI P-value

(Intercept) 5.3542861 1.177844e-03

factor(cls)2 0.1195679 1.354649e-08

#### Reference:

- 1. Hastie TJ, Pregibon D. *Generalized linear models* in *Statistical Models in S* eds Chambers JM, Hastie TJ. 1992, Wadsworth&Brooks/Cole.
- 2. R Development Core Team. Stats 2.2.1, R package, <a href="http://www.r-project.org/">http://www.r-project.org/</a>
- 3. Venables WN, Ripley BD. *Generalized linear models* in *Modern Applied Statistics* with S-PLUS, 3<sup>rd</sup> Ed. 1999, Springer, New York.

#### Parameters:

Name	Description	Choices
input clin data filename	clinical datatxt	
	Format shown below.	
input cls filename	class information filecls	
	Format described in GenePattern File	
	Formats.	
output file	Name for the output file.	

response variable  Column name for the response/independent variable. Must be a column in the input clin data file.  Variable continous  Comma separated list of the continuous dependent variables (e.g. age) to use for the analysis. Each variable must be a column in the input clin data file.  Variable category  Comma separated list of the categorical dependent variables (e.g. gender) to use for the analysis. Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  Variable interaction terms  Separate interaction variables with a colon (e.g. sex:cls). Separate sets of interaction variables with a comma (e.g. sex:cls, sex:grade). Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  input subgroup  Analyze a subgroup of the data. Identify the subgroup by specifying a variable followed by a colon and a value for the variable. For example: gender:M or cls:1).  variable selection  Select the way dependent variables are entered into the model. Use the default Stepwise selection  Entered relection			
be a column in the input clin data file.  Variable continous  Comma separated list of the continuous dependent variables (e.g. age) to use for the analysis. Each variable must be a column in the input clin data file.  Variable category  Comma separated list of the categorical dependent variables (e.g. gender) to use for the analysis. Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  Variable interaction terms  Separate interaction variables with a colon (e.g. sex:cls). Separate sets of interaction variables with a comma (e.g. sex:cls, sex:grade). Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  input subgroup  Analyze a subgroup of the data. Identify the subgroup by specifying a variable followed by a colon and a value for the variable. For example: gender:M or cls:1).  variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection	response variable	Column name for the	
variable continous  Comma separated list of the continuous dependent variables (e.g. age) to use for the analysis. Each variable must be a column in the input clin data file.  Variable category  Comma separated list of the categorical dependent variables (e.g. gender) to use for the analysis. Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  Variable interaction terms  Separate interaction variables with a colon (e.g. sex:cls). Separate sets of interaction variables with a comma (e.g. sex:cls, sex:grade). Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  input subgroup  Analyze a subgroup of the data. Identify the subgroup by specifying a variable followed by a colon and a value for the variable. For example: gender:M or cls:1).  variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection		response/independent variable. Must	
dependent variables (e.g. age) to use for the analysis. Each variable must be a column in the input clin data file.  Variable category  Comma separated list of the categorical dependent variables (e.g. gender) to use for the analysis. Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  Variable interaction terms  Separate interaction variables with a colon (e.g. sex:cls). Separate sets of interaction variables with a comma (e.g. sex:cls, sex:grade). Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  input subgroup  Analyze a subgroup of the data. Identify the subgroup by specifying a variable followed by a colon and a value for the variable. For example: gender:M or cls:1).  variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection		be a column in the input clin data file.	
for the analysis. Each variable must be a column in the input clin data file.  Variable category  Comma separated list of the categorical dependent variables (e.g. gender) to use for the analysis. Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  Variable interaction terms  Separate interaction variables with a colon (e.g. sex:cls). Separate sets of interaction variables with a comma (e.g. sex:cls, sex:grade). Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  input subgroup  Analyze a subgroup of the data. Identify the subgroup by specifying a variable followed by a colon and a value for the variable. For example: gender:M or cls:1).  variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection	variable continous	Comma separated list of the continuous	
a column in the input clin data file.  Variable category  Comma separated list of the categorical dependent variables (e.g. gender) to use for the analysis. Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  Variable interaction terms  Separate interaction variables with a colon (e.g. sex:cls). Separate sets of interaction variables with a comma (e.g. sex:cls, sex:grade). Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  input subgroup  Analyze a subgroup of the data. Identify the subgroup by specifying a variable followed by a colon and a value for the variable. For example: gender:M or cls:1).  variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection		dependent variables (e.g. age) to use	
variable category  Comma separated list of the categorical dependent variables (e.g. gender) to use for the analysis. Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  variable interaction terms  Separate interaction variables with a colon (e.g. sex:cls). Separate sets of interaction variables with a comma (e.g. sex:cls, sex:grade). Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  input subgroup  Analyze a subgroup of the data. Identify the subgroup by specifying a variable followed by a colon and a value for the variable. For example: gender:M or cls:1).  variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection		for the analysis. Each variable must be	
dependent variables (e.g. gender) to use for the analysis. Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  variable interaction terms  Separate interaction variables with a colon (e.g. sex:cls). Separate sets of interaction variables with a comma (e.g. sex:cls, sex:grade). Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  input subgroup  Analyze a subgroup of the data. Identify the subgroup by specifying a variable followed by a colon and a value for the variable. For example: gender:M or cls:1).  variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection		a column in the input clin data file.	
use for the analysis. Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  variable interaction terms  Separate interaction variables with a colon (e.g. sex:cls). Separate sets of interaction variables with a comma (e.g. sex:cls, sex:grade). Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  input subgroup  Analyze a subgroup of the data. Identify the subgroup by specifying a variable followed by a colon and a value for the variable. For example: gender:M or cls:1).  variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection	variable category	Comma separated list of the categorical	
be a column in the input clin data file or cls (to use the classes in the input cls file).  variable interaction terms  Separate interaction variables with a colon (e.g. sex:cls). Separate sets of interaction variables with a comma (e.g. sex:cls, sex:grade). Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  input subgroup  Analyze a subgroup of the data. Identify the subgroup by specifying a variable followed by a colon and a value for the variable. For example: gender:M or cls:1).  variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection		dependent variables (e.g. gender) to	
cls (to use the classes in the input cls file).  variable interaction terms  Separate interaction variables with a colon (e.g. sex:cls). Separate sets of interaction variables with a comma (e.g. sex:cls, sex:grade). Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  input subgroup  Analyze a subgroup of the data. Identify the subgroup by specifying a variable followed by a colon and a value for the variable. For example: gender:M or cls:1).  variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection		use for the analysis. Each variable must	
variable interaction terms  Separate interaction variables with a colon (e.g. sex:cls). Separate sets of interaction variables with a comma (e.g. sex:cls, sex:grade). Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  input subgroup  Analyze a subgroup of the data. Identify the subgroup by specifying a variable followed by a colon and a value for the variable. For example: gender:M or cls:1).  variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection		be a column in the input clin data file or	
variable interaction terms  Separate interaction variables with a colon (e.g. sex:cls). Separate sets of interaction variables with a comma (e.g. sex:cls, sex:grade). Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  input subgroup  Analyze a subgroup of the data. Identify the subgroup by specifying a variable followed by a colon and a value for the variable. For example: gender:M or cls:1).  variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection		cls (to use the classes in the input cls	
colon (e.g. sex:cls). Separate sets of interaction variables with a comma (e.g. sex:cls, sex:grade). Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  input subgroup  Analyze a subgroup of the data. Identify the subgroup by specifying a variable followed by a colon and a value for the variable. For example: gender:M or cls:1).  variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection		file).	
interaction variables with a comma (e.g. sex:cls, sex:grade). Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  input subgroup  Analyze a subgroup of the data. Identify the subgroup by specifying a variable followed by a colon and a value for the variable. For example: gender:M or cls:1).  variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection	variable interaction terms	Separate interaction variables with a	
sex:cls, sex:grade). Each variable must be a column in the input clin data file or cls (to use the classes in the input cls file).  input subgroup  Analyze a subgroup of the data. Identify the subgroup by specifying a variable followed by a colon and a value for the variable. For example: gender:M or cls:1).  variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection		colon (e.g. sex:cls). Separate sets of	
be a column in the input clin data file or cls (to use the classes in the input cls file).  input subgroup  Analyze a subgroup of the data. Identify the subgroup by specifying a variable followed by a colon and a value for the variable. For example: gender:M or cls:1).  variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection		interaction variables with a comma (e.g.	
cls (to use the classes in the input cls file).  Analyze a subgroup of the data. Identify the subgroup by specifying a variable followed by a colon and a value for the variable. For example: gender:M or cls:1).  variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection		sex:cls, sex:grade). Each variable must	
input subgroup  Analyze a subgroup of the data. Identify the subgroup by specifying a variable followed by a colon and a value for the variable. For example: gender:M or cls:1).  Variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection		be a column in the input clin data file or	
input subgroup  Analyze a subgroup of the data. Identify the subgroup by specifying a variable followed by a colon and a value for the variable. For example: gender:M or cls:1).  Variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection		cls (to use the classes in the input cls	
the subgroup by specifying a variable followed by a colon and a value for the variable. For example: gender:M or cls:1).  variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection		file).	
followed by a colon and a value for the variable. For example: gender:M or cls:1).  Variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection	input subgroup	Analyze a subgroup of the data. Identify	
variable. For example: gender:M or cls:1).  Variable selection  Select the way dependent variables are entered into the model. Use the default  Stepwise selection		the subgroup by specifying a variable	
cls:1).  Variable selection  Select the way dependent variables are entered into the model. Use the default Stepwise selection		followed by a colon and a value for the	
variable selection  Select the way dependent variables are entered into the model. Use the default Stepwise selection		variable. For example: gender:M or	
entered into the model. Use the default Stepwise selection		cls:1).	
	variable selection	Select the way dependent variables are	Default: no
value unloss you are familiar with Forward selection		entered into the model. Use the default	Stepwise selection
value unless you are familial with Polward selection		value unless you are familiar with	Forward selection
clinical data analysis. Backward selection		clinical data analysis.	Backward selection

# Format of input clinical data file:

Tab-delimited text file. The first row contains column heads. The first column must be the sample identifier; the column head is your choice; the order of samples in this file

and the input cls file must match. Each subsequent column contains a clinical variable. For example:

name	time	censor	cls.clinical	labdata1	labdata1	age	sex	grade
case1	207	0	poor	0.9	430	72	1	4
case4	49	0	poor	2.7	220	54	1	4
case5	267	0	poor	28.7	500	53	1	4
case7	8	0	poor	2.4	1090	75	0	4

Identify continuous (e.g., age) or categorical (e.g., sex) dependent variables for the analysis by entering the column heads in the *variable continuous* or *variable category* fields, respectively. Identify the response/independent variable (e.g. cls.clinical) for the analysis by entering the column head in the *response variable* field.

### **Example input files:** <u>surv.txt</u>, <u>surv.cls</u>

The example files contain mock data. To run an analysis using these files, enter the column head "cls.clinical" in the *response variable* field and "cls" in the *variable* category field.

## **Output files:**

LogisticRegression result.txt: summary of the results.

### Platform dependencies:

task type: Survival Analysis

**CPU type:** any **OS:** any

**Language:** R (version 2.2.1 or above)

Suppot files: none